






VERTICAL SECTION



HORIZONTAL SECTION



FEATURES



RECYCLED PVC

Windows are manufactured using high-quality recycled PVC - biodegradable, recyclable, non-toxic, fire-resistant, and eco-friendly.



ENERGY GLASS INSULATING UNIT

The insulating glass unit features a black warm-edge spacer and Planitherm Infinity low-emissivity and selective coating by Saint-Gobain.



PERFECT WELDING

The welding technology completely eliminates the weld bead from the corners.



HARDWARE

Adjustable three-dimensional hinges with silver-colored PVC hinge covers. Lever rod for the upper and lower locking of the passive sash. Upon request, concealed hardware can be integrated. Silver steel cremonese bolt with three anti-burglary locking points.



TOULON HANDLE

The Toulon handle by Hoppe is crafted from premium materials sourced from certified manufacturers.



SECURITY

All our product lines are equipped with certified hardware. Additionally, the integrated electronic contact alarm system is compatible with all home automation systems.



WIDE RANGE OF COLORS

The regenerated PVC base body is available in various colors, allowing for the combination of 42 decorative films from the REHAU color chart, achieving the desired aesthetic for any project.



WARRANTIES

Thanks to the performance and reliability of its windows, PBFinestre has earned prestigious certifications from International Institutes. All products are covered under legal warranty.

TECHNICAL DATA

Air Permeability Resistance Class *

(according to the UNI EN 1026 – 2001 test standard and the UNI EN 12207 – 2000 classification standard)

Water Tightness Resistance Class *

(according to the UNI EN 1027 – 2001 test standard and the UNI EN 12208 – 2000 classification standard)

Wind Load Resistance Class*

(according to the UNI EN 12211 – 2001 test standard and the UNI EN 12210 – 2000 classification standard)

Acoustic Reduction Certification**

Thermal Performance Certifications **

Class 4

Indicates how much the fixture is permeable to air passing through it at a pressure of 600 Pa, which corresponds to a wind speed of 115 km/h.

9A

Indicates the fixture's ability not to be penetrated by water under a pressure of 600 Pascal.

class B3

Indicates the fixture's ability to resist the wind pressure at a specific speed.

up to 40 dB

(with 44.1 Stadip Silence glass Planitherm Infinity + 16 Argon gas + 33.1 Stadip Protect - 51 mm thick sections)

Achievable U_w values: **1.3 W/m²K** in the version with a thickness of 51mm

Solar Factor **G=0,35**



Products conforming to the European standard EN 14351-1.

All our windows are CE marked, according to the law.

*As per certifications in our possession issued by the ROSENHEIM Institute

**As per certification in our possession issued by the GIORDANO Institute



Descriptions are not binding. The company reserves the right to make any necessary modifications. PB FINESTRE WINDOWS AND DOORS is a trademark owned by IWDT SRL a socio unico. All rights reserved.